

ATLAS 1**BETONFİBER**[®]
Makro & Mikro Donatılar

BETONFİBER® BF0960 ÇELİK FİBER		BETONFİBER® BF0960 STEEL FIBER	
Standart	ASTM A820/A820M - 04, Type 1 cold drawn wire	Standard	ASTM A820/A820M - 04, Type 1 cold drawn wire
Görünüm	Parlak, Çelik Tel	Appearance	Shiny, steel fibers
Tip	Soğuk Çekme	Type	Cold-drawn
Kenar	Kıvrımlı	Side	Twisted
Açı	45°	Angle	45°
Fiber Uzunluk	60 mm	Fiber Length	60 mm
Çap	0.9 mm	Diameter	0.9 mm
Çekme Mukavemeti	1100 Mpa	Tensile Strength	1100 Mpa
Narinlik oranı	66	Aspect Ratio	66
Paketleme	20 kg ya da 25 kg	Packaging	20 or 25 kgs
Palet Kilogram	1 Tonluk Palet (25 kilogramlık torba, 40 torba palette) (20 kilogramlık torba, 50 torba palette)	Pallets	1 pallet is equal to 1 tone. (25 kg's, 40 packets-20 kg's,50 packets)

BETONFİBER[®]
Makro & Mikro Donatılar

İnönü Mahallesi Alpkaya Caddesi No:6 Ataşehir / İstanbul Tel: +90 216 386 84 00 Fax: +90 216 386 84 08

BETONA DEĞER KATAR**BETONFİBER.COM**